

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁵ : E21B 25/00, 49/02</p>	<p>A1</p>	<p>(11) International Publication Number: WO 94/28281 (43) International Publication Date: 8 December 1994 (08.12.94)</p>
<p>(21) International Application Number: PCT/NO94/00095 (22) International Filing Date: 19 May 1994 (19.05.94) (30) Priority Data: 931865 24 May 1993 (24.05.93) NO (71)(72) Applicant and Inventor: BERG, Egil [NO/NO]; Boganeset 20, N-4030 Hinna (NO). (72) Inventor; and (75) Inventor/Applicant (for US only): TORGRIMSEN, Tor [NO/NO]; Stasjonsveien 26 A, N-4018 Stavanger (NO). (74) Agents: HÅMSØ, Borge et al.; Håmsø Patentbyrå, P.O. Box 171, N-4301 Sandnes (NO).</p>		<p>(81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KG, KP, KR, KZ, LK, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>
<p>(54) Title: A DEVICE FOR CORE DRILL</p> <p>(57) Abstract</p> <p>A core pipe (3) for coring or core drilling, especially with sampling in connection with oil wells, wherein the core pipe (3) is rotatively suspended from a rotary drill pipe (1) operating a bit (2), and further provided with internal, telescopically disposed core pipes (5, 6), rupture pins (7, 8) retain the core pipes (5, 6) in the initial positions thereof. When core material (10) strikes against a stop (9) at the upper end of the core pipe (6), or wedges itself or get stuck within the core pipe (6), the rupture pin (7) is cut off and the core pipe (6) follows the core material (10), the core pipe (6) then sliding within the core pipe (5). Should the core material (10) get wedged in the core pipe (5) beneath the core pipe (6), rupture pin (8) is cut off, the core pipe (5) then following the core material (10) upwardly within the outer core pipe (3).</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

A DEVICE FOR CORE DRILL

The invention relates to a core pipe for a core drill.

Core samples are an important information source in geological analyses, and such samples are frequently used in connection with the drilling for oil. Core samples are fetched from the ground by means of a core drill provided with an internal core pipe. In connection with oil wells, it is usual to use a core drill capable of taking samples having a length of up to 30 metres. However, in some geological formations, it is difficult to achieve core samples having full length, the core getting stuck in the core drill, and the sampling has to be interrupted.

A typical core drill for use in oil wells has an external rotating drill pipe driving the bit, and an internal stationary core pipe. The core pipe is located straight above the bit and, at the upper end thereof, it is suspended from the drill pipe in a mounting allowing the drill pipe to rotate in relation to the core pipe. An intermediately open bit is used and, during drilling, core material comes up through the bit and passes further upwardly within the core pipe. The core pipe has a slightly larger internal diameter than that of the opening in the bit, such that some clearance exists between the core material and the core pipe. Often, wedging is caused by breakage of the core at transition(s) between various zones of the ground. As the breakage surface seldom is perpendicular to the core axis, the axial force

causes parts of the core to be pressed outwardly against the wall of the core pipe, resulting in the core material becoming wedged within the core pipe. Bulging clay or loose sand may also cause the core to be stuck. The drilling equipment must be pulled out from the hole, and stuck core material must be removed before the sampling may be continued. Such extra operations extends the operational time with sampling substantially, and significant further costs accumulate.

The object of the invention is to provide a core pipe, where wedging can be allowed in a certain degree, without having to interrupt the coring operation.

The object is achieved by the features as defined in the following claims.

An example of an embodiment of the invention is described in the following, reference being made to the attached drawings, in which:

Figure 1 diagrammatically and sectioned in the lower portion shows a drill pipe having an internal telescopic core pipe, as seen in the initial position;

Figure 2 diagrammatically and sectioned shows the telescopic core pipe after core material has got wedged at two places.

In figure 1, reference numeral 1 denotes a drill pipe having a bit 2 for coring operation (core drilling). A core pipe 3 is suspended from the drill pipe 1 in a fastener 4, which may rotate in relation to the drill pipe. The fastener 4 is a part of a usual known suspension device (hanger) for core pipes and, therefore, the fastener 4 is not shown in detail. Internally within the core pipe 3, two further core pipes 5 and 6 are concentrically and telescopically disposed. The core pipe 5 is adapted to be displaced axially within the core

pipe 3, and the innermost core pipe 6 may similarly be axially displaced within the outer core pipe 5. In the initial position, the internal core pipes 5 and 6 occupy positions at the lower end of the outer core pipe 3, and they are kept in place in relation to the core pipe 3 by rupture pins 7 and 8. At the upper end thereof, the core pipe 6 is provided with a stop 9 adapted to prevent core material 10 from passing.

When drilling, the core material 10 will pass through the bit 2 and into the inner core pipe 6 and further upwardly to rest against the stop 9, so that axial force is transferred to the rupture pin 7 which then is cut off. The core pipe 6 will thereafter follow the core material 10 upwardly, the core pipe 6 sliding within the core pipe 5. Should the core material 10 become wedged within the core pipe 6 prior to the core material 10 coming to rest against the stop 9, the rupture pin 7 will be cut off earlier because of the axial force transferred through the wedging, and the core pipe 6 will follow wedged to the core material 10. Therefore, the drilling may be continued.

If the core material 10 also should get stuck to the core pipe 5, below the lower end of the core pipe 6, the rupture pin 8 is also cut off. Then, the core pipe 5 will, in the same way as the core pipe 6, follow the core material 10 upwardly, the core pipe 5 sliding internally within the core pipe 3. Therefore, the drilling may still be continued. A similar situation is shown in figure 2, in which the core material 10 has become stuck in both the internal core pipes 5 and 6.

Should a third wedging occur, namely against the outer core pipe 3, the situation is the very same as with known core pipes, and the coring has to be interrupted. In particularly difficult formations, it might be of interest to widen the telescopic action, adding more internal concentric core pipes, thereby enabling a larger number of wedgings to be

handled.

The rupture pins 7, 8 are dimensioned for the force the core is assumed to stand before it is destroyed. Instead of the rupture pins 7, 8, the core pipes 5, 6 might be kept in their initial positions by means of flux material such as glue or soldering flux adapted to be cut off upon the occurrence of a predetermined axial force. Alternatively, the core pipes 5, 6 may be attached in the initial positions thereof to the core pipe 3, using a friction connection, e.g. in the form of a press fit adapted to slide at a predetermined axial force.

C l a i m s

1. A core pipe (3) for coring operations, especially with sampling in connection with oil wells, wherein the core pipe (3) is rotatively suspended internally within a drill pipe (1), so that the drill pipe (1) can rotate without the core pipe (3) rotating, c h a r a c t e r i z e d i n that the core pipe (3) is provided with one or more internal, concentrically arranged core pipes (5, 6), each of the internal core pipes (5, 6) being adapted to be displaced axially within the closest external core pipe, and wherein the innermost core pipes (5, 6) are retained in initial positions close to the lower end of the outer core pipe (3) through an attaching device adapted to release when the core pipes (5, 6) are subjected to a predetermined force.

2. A core pipe (3) as set forth in claim 1, c h a r a c t e r i z e d i n that the innermost core pipe (6), at the top end thereof, is provided with a stop (9) adapted to prevent core material (10) from passing.

3. A core pipe (3) as set forth in claims 1 and 2, c h a r a c t e r i z e d i n that the innermost core pipes (5, 6) are retained in initial positions close to the lower end of the outer core pipe (3) by means of rupture pins (7, 8) adapted to be cut off upon the occurrence of a predetermined force.

4. A core pipe (3) as set forth in claims 1 and 2, c h a r a c t e r i z e d i n that the innermost core pipes (5, 6) are retained in initial positions close to the lower end of the outer core pipe (3) by means of an aggregate or flux material adapted to be ruptured upon the occurrence of a predetermined force.

5. A core pipe (3) as set forth in claims 1 and 2, c h a r a c t e r i z e d i n that the innermost core pipes (5, 6) are retained in initial positions close to the

lower end of the outer core pipe (3) by means of a frictional connection adapted to be overcome upon the occurrence of a predetermined force.




Fig. 1


$2/2$ 

Fig. 2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 94/00095

A. CLASSIFICATION OF SUBJECT MATTER

IPC5: E21B 25/00, E21B 49/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC5: E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

CLAIMS, WPAT

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 2032423 (L.A. LARSON ET AL), 3 March 1936 (03.03.36), the whole document --	1-5
A	US, A, 2929612 (F.L. LE BUS, SR), 22 March 1960 (22.03.60), the whole document --	1-5
A	DE, B, 1167286 (BERGWERKSVERBAND G.M.B.H.), 9 April 1964 (09.04.64), the whole document --	1-5

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

26 August 1994

Date of mailing of the international search report

02 - 1994

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Christer Bäcknert
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 94/00095

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR, A, 1474299 (J.M. HUBER CORPORATION), 24 March 1967 (24.03.67), figure 1, details 36-38 and corresponding text in columns 2 and 3 -- -----	1-5

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/07/94

International application No.
PCT/NO 94/00095

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 2032423	03/03/36	NONE	
US-A- 2929612	22/03/60	NONE	
DE-B- 1167286	09/04/64	NONE	
FR-A- 1474299	24/03/67	NONE	